

Atlas Copco LPD-HD-RV Post Driver

Prod Code: 6040-ATLA-24422

LPD-HD-RV comes with a standard 0.5 m quick release coupling tail hose. It can be operated remotely The LPD-HD-RV is greate for driving in road barrier tubes, profiles, signposts and awide range of anchors and poles.

* Adaptor to be purchased seperately

SPECIFICATIONS	
Post/rod diameters	70-150mm
Activation type	remote valve
Hydraulic system	Open or closed centre
Service weight	46kg
Oil flow	28-40 l/min
Working pressure	105-125 bar
Impact rage	1 320 (30 l/min)
Vibration level 3 axes	12.8m/s
Sound power level guaranteed (2000/14/EC)	118Lw dB(A)



Solid adaptors for LPD-HD-T and LPD-HD-RV

Shape	Description	Part.mimber
Round	Rold' tubes and 347 mm (5.51 m) golies.	00714060.52
Round	Pondam 135-145 mm (531-571 m) tutes	33*1 8662 53
Round	Pondiam (185-125 mm)/4.15-4.83 in(1.046	1171 8665 54
Round	Rondam 150 mm (5.91 m) poles	1171.0000.55

GearGB Hart Industrial Tools White Hart Court, Hart Village, Hartlepool TS27 3AW