

Atlas Copco LP9-20P 20 L/Min Hydraulic Pack + LH230E Breaker

Prod Code: 6040-ATLA-350

You can use the Atlas Copco power packs virtually anywhere: fitted with wheels and handles, they are easy to manoeuvre around building sites. They are easy to start, the noise level is low, and when they are not in use, the power packs are small enough to be stored on shelves. They are also lightweight enough that two people can lift one up and fit it in the back of a van.

This power packs is equipped with Power On Demand (POD). This hydraulic regulatory system automatically idles the engine when the tool is not being used and speeds it up when the tool is activated.

BREAKER.

This medium weight, multipurpose breaker is among the best general purpose breakers available in the 22-28 kg (48-62 lb) range. It is commonly used with 5" asphalt chisels for road building maintenance applications, but also work well in brickwork, frozen soil and concrete.



SPECIFICATIONS

| | |
|---|-------------------------|
| Honda | GX270 |
| HP | 9 |
| Oil flow | 20 l per min |
| Weight (incl oil) | 80 kg |
| Length | 630 mm |
| Width | 530 mm |
| Height | 640 mm |
| Max pressure | 150 bar |
| Fuel capacity | 6 l |
| Hose included | YES |
| Power on Demand (POD) | YES |
| Oil control: engine oil | YES |
| Electric start | NO |
| Sound power level guaranteed L _w (2000/14/EC)* | 101 dB(A) |
| Sound pressure level (ISO 11203)* L _{p r 1m} | 87 dB(A) |
| EHTMA class | C |
| Breaker Weight incl hoses | 28 kg |
| Breaker Version | Vibro-reduced |
| Shank Size (mm) | 32x152 |
| Length | 735 mm |
| Oil flow | 20 - 30 l/min |
| Working pressure | 105 - 125 bar |
| Back Pressure max | 15 bar |
| Impact rate | 1500 2100 blows Per min |
| Vibration level 3 axes (ISO 28927-5) 10 lpm* | 4.6 m/s |
| Sound power level guaranteed L _w (2000/14/EC)* | 107 dB(A) |
| Sound pressure level (ISO 11203)* L _{p r 1m} | 95 dB(A) |